

Model: AGB4573ZTZ (TAGP4573Z)

Product Description

Type: Reciprocating
Application: HBP - High Back Pressure
Refrigerant: R-404A
Voltage/Frequency: 440V 3~ 60Hz 400V 3~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power W	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W		Btu/Wh	kcal/Wh	W/W					
EN12900	440V 3~ 60HZ	68553	17275	20086	7831	8.75	2.21	2.56	5°C (41°F)	45°C (113°F)	32°C (90°F)	15°C (59°F)	45°C (113°F)
EN12900	400V 3~ 50HZ	57130	14397	16739	6526	8.75	2.21	2.56	5°C (41°F)	45°C (113°F)	32°C (90°F)	15°C (59°F)	45°C (113°F)

General

Evaporating Temp. Range: -6.7°C to 12.8°C (20°F to 55°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 49
Weight Unit of Measure: KG
Displacement (cc): 135
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 1960

Electrical

Voltage Range (50 Hz): 340-440
Voltage Range (60 Hz): 396-499
Locked Rotor Amps (LRA): 61
Rated Load Amps (RLA 50 Hz): 10.7
Rated Load Amps (RLA 60 Hz): 13.4
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: 2.2
Motor Resistance (Ohm) - Start: 2.2
Motor Type: 3PH
Overload Type: N/A
Relay Type: N/A

Agency Approval

CCC Listed, CE Listed, GOST RUSSIA Listed, GOST
UKRAINE Listed, IRAM Listed, SASO Listed, UL
Recognized, cURus Recognized