



tecumseh

SILAG2525P-TX

400V 3~ 50Hz

Condensing unit

HSL2525P-TX0F6HA

LBP

R-404A / R-452A / R-454C / R-455A

Voltage Code : TX

Refrigerant	Frequency	Nominal Cooling Capacity (*)	
		Watts	BTU/h
R-448A	50HZ	3303	11264
R-449A	50HZ	3232	11020
R-454C	50HZ	2787	9502
R-455A	50HZ	2956	10081

(*) Operating conditions Custom : Mid / T°Ambient 32°C / T°Evap -30°C

T°Return gas temp. -22°C / T°Superheat 7K / T°Subcooling 2K



*Non-contractual picture

Dimensions

Weight	108 kg (238 lb)
Length	1170 mm (46.1 in)
Width	570 mm (22.4 in)
Height	710 mm (28 in)
Ø Suction Tube	7/8 in (22.2mm)
Ø Discharge Tube	1/2 in (12.7mm)

Certificates



General

Condensing Unit Type	Outdoor
Family Condensing Unit	Silensys
Horse Power	6 hp
Design Ambient Temp °C (°F)	+43°C / +110°F
Evaporating Temp. Range	-40°C to -10°C (-40°F to 14°F)
Expansion Device	Expansion Valve
Compressor Model	1 x AG2525P-TZ1A
Fan Diameter	1 x 450 mm
Fan Technology	EC Technology
Condenser Technology	Fin and Tube
Condensing Unit IP	IPX4

Electrical

Motor Type	3PH
Current RLA 50Hz (A)	7.92
Current LRA (A)	61
Overload	35HM-235-4
- Time Check	2s - 10s / 36 A
- Open Temp / Close Temp	115 °C / 61 °C

Pressure Equipment Directive

PED Category	Category II
Maximum BP Pressure	17 bar
Maximum HP Pressure	32 bar
CE Record Number	0082

Note : Tecumseh reserves the right to change information contained in this document without notification.