

FEINROHREN GREEN

Cu-DHP copper tubes according to the standard EN 12735-1

Working Pressure according to EN 14276/2020, up to 100° C

Designed Temper R 200

Safety Coefficient 3

Supplied Temper R 220 and R 290



Naturally dynamic

FEINROHREN GREEN

OD	OD	WT	WP
mm	inches	mm	Bar
6,35	1/4	0,80	171
9,52	3/8	0,80	109
		1,00	134
12,70	1/2	0,80	80
		1,00	98
		1,25	125
15,87	5/8	0,80	63
		1,00	77
		1,05	81
		1,55	124
19,05	3/4	0,80	52
		1,00	62
		1,25	79
		1,30	82
		1,85	120
22,22	7/8	1,00	53
		1,25	67
		1,50	81
		2,20	123
25,40	1	1,00	46
28,57	1 1/8	1,00	41
		1,25	52
		1,65	69
		1,95	82
		2,80	121
31,75	1 1/4	1,25	46
34,92	1 3/8	1,25	42
		1,65	56
		1,80	61
		2,35	81
		3,40	120
41,27	1 5/8	1,25	35
		1,65	47
		2,00	57
		2,10	60
		2,75	80
		4,05	121
53,97	2 1/8	1,25	27
		1,65	36
		2,00	43
66,67	2 5/8	1,65	29
		2,10	37
79,37	3 1/8	1,65	24
		2,50	37
92,07	3 5/8	2,50	32
104,77	4 1/8	2,70	30
108,00		2,50	27
133,00		3,00	26
159,00		3,00	22



Naturally dynamic