

Functions	Lock 100	Lock 200	Central Lock	Virtual Central Lock*
TOSIBOX® Plug & Go™ Technology	Yes	Yes	Yes	Yes
Mounting options	DIN rail mounting at bottom	DIN rail mounting on three sides	19" rack mounting, rails included	No
Power input	12 - 24V DC, ±25%	8 - 27 V DC ±10%, with cable anchor	90 - 264 V AC	No
3G / 4G USB modem support	Yes	Yes	No	No
WAN port	10/100 Mbit/s	10/100 Mbit/s	1 Gbit/s	One required, dependent on virtual platform
LAN ports	3 x 10/100 Mbit/s, bridged	3 x 10/100 Mbit/s, bridged	4 x 1 Gbit/s, independent	One or more, dependent on virtual platform
VPN throughput	Up to 6 Mbit/s	Up to 15 Mbit/s	Up to 700 Mbit/s	Dependent on virtual platform
VPN encryption	Blowfish 128 bit CBC, AES 128/192/256 bit CBC			
VPN connection authentication	PKI, 3072 bit RSA			
Concurrent VPN connections	Max 10	Max 50	Max 4000	Dependent on virtual platform and license
Supported platforms	No	No	No	VMWare ESXi, Microsoft Hyper-V or Linux KVM
TosiOnline™ – automatic connection recovery functionality	Yes	Yes	No	No
PoE functionality	No	PoE in and PoE out: 27 V / 580 mA max	No	No
CE approval	Yes	Yes	Yes	No
FCC approval	Yes	Yes	Yes	No
UL approval	No	Yes	Yes	No
WLAN	802.11b/g/n	No	No	No
Product code	TBL1	TBL2	TBCL1	TBVCL1

^{*} please see all requirements on VCL datasheet

TOSIBOX® Key 100, Key 200, Mobile Client

Functions	Key 100	Key 200
TOSIBOX® Plug & Go™ Technology	Yes	Yes
Cryptographic key size and type	2048 bit RSA, hardware-based	2048 bit RSA, hardware-based
Mobile Client for Android and iOS	Yes (1 license incl.)	Yes (1 license incl.)
Product code	TBK1	TBK2

All TOSIBOX® products are fully compatible with other TOSIBOX® products.

Download the TOSIBOX® Mobile Client app

or Took
Google Play

or Download on the
App Store





Do you want to secure your business? Contact us! Find your nearest retailer / distributor at tosibox.com

sales@tosibox.com support@tosibox.com Sales within Finland, tel. 044 70 90 100 Sales, international tel. +358 44 70 90 200 www.tosibox.com